




<p>WHMIS (Canada)</p>  <p>D-2A D-2B</p>	<p>NFPA (USA)</p> <p>Fire</p>  <p>Health Reactivity</p> <p>Specific hazard</p>	<p>HMS (USA)</p> <table border="1"> <tr> <td>Health hazards</td> <td>* 1</td> </tr> <tr> <td>Flammability</td> <td>1</td> </tr> <tr> <td>Physical hazards</td> <td>0</td> </tr> <tr> <td>Personal protection</td> <td>X</td> </tr> </table>	Health hazards	* 1	Flammability	1	Physical hazards	0	Personal protection	X	<p>Protective clothing</p> 
Health hazards	* 1										
Flammability	1										
Physical hazards	0										
Personal protection	X										

Section 1. Chemical product and company identification	
Trade name	CP-10000
Product type	Color Paste
Chemical family	Coloring material.
Material uses	Used in the manufacture of thermoset plastic parts.
Manufacturer	<p>AOC, LLC 950 Highway 57 East Collierville, TN U.S.A. 38017 Website: www.aoc-resins.com Phone Number: (901) 854-2800 8am-5pm (Central Time) Mon-Fri</p>
In case of emergency	<p>CHEMTREC (US): 24 hours/7 days (800) 424-9300 CANUTEC (Canada): 24 hours/7 days (613) 996-6666</p>

Section 2. Hazards identification	
OSHA status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Routes of entry	Skin contact. Eye contact. Ingestion.
Potential acute health effects	This product may irritate eyes and skin upon contact. Prolonged exposure may cause dermatitis. While ingestion is unlikely it may cause irritation to gastrointestinal tract. May cause nausea, diarrhea, or vomiting.
Potential chronic health effects	<p>CARCINOGENIC EFFECTS: <u>Titanium Dioxide</u>: Classified A4 (not classifiable for human or animal) by ACGIH. Classified 2B (possible for human) by IARC. <u>Silica, Gel</u>: Classified 3 (not classifiable for human) by IARC. <u>Silica, Amorphous</u>: Classified 3 (not classifiable for human) by IARC. <u>Aluminum Oxide</u>: Classified A4 (not classifiable for human or animal) by ACGIH. <u>Zirconium Oxide</u>: Classified A4 (not classifiable for human or animal) by ACGIH. MUTAGENIC or TERATOGENIC EFFECTS: No known effect according to our database.</p>

Section 3. Composition/information on ingredients		
Name	CAS #	% by weight
1) Titanium Dioxide	13463-67-7	60 - 100
2) Silica, Gel	112926-00-8	5 - 10
3) Silica, Amorphous	7631-86-9	5 - 10
4) Aluminum Hydroxide	21645-51-2	5 - 10
5) Aluminum Oxide	1344-28-1	1 - 5
6) Zirconium Oxide	1314-23-4	1 - 5

Section 4. First aid measures

Eye contact	Flush with a continuous flow of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Use of buffered baby shampoo will aid in removal. Seek medical attention.
Skin contact	Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. If irritation persists, seek medical attention.
Inhalation	Move the victim to a safe area as soon as possible. Allow the victim to rest in a well-ventilated area. If breathing is difficult, give oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Ingestion	Remove dentures if any. Have conscious person drink several glasses of water or milk. Induce vomiting (by qualified person only). Lower the head so that vomit will not re-enter the mouth and throat. Never give an unconscious person anything to ingest. Seek medical attention.

Section 5. Fire fighting measures

The product is:	Combustible liquid, Class IIIB.
Auto-ignition temperature	Not available.
Flash point	240°F (116°C)
Flammable limits	Not available.
Products of combustion	May produce carbon monoxide, carbon dioxide, and irritating or toxic vapors, gases or particulate. If product contains metal compounds, the toxic fumes may contain fumes of that metal. See Section II.
Fire hazard	No specific information is available in our database.
Explosion hazard	No specific information is available in our database regarding the product's risks of explosion in the presence of various materials.
Fire-fighting media and instructions	SMALL FIRE: Use carbon dioxide, foam, dry chemical or water fog to extinguish. LARGE FIRE: Evacuate surrounding areas. Use carbon dioxide, foam, dry chemical or water fog to extinguish. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Prevent run off to sewers or other water ways.

Section 6. Accidental release measures

Small spill	Absorb with an inert material and place in an appropriate waste disposal container.
Large spill	Stop leak if without risk. Eliminate all ignition sources. Contain with an inert material, recover as much as possible and place the remainder in an appropriate waste disposal container. Warn unauthorized personnel to move away. Prevent entry into sewers or confined areas.

Section 7. Handling and storage

Handling	CAUTION Use only in well-ventilated areas. Avoid inhalation and contact with eyes, skin, and clothing. Wear appropriate personal protective equipment for your task. Prevent prolonged or repeated skin contact. Note: If product contains metal compounds (Section III), avoid dust from dried product or grinding of articles made from this material.
Storage	Keep container dry. Containers should be grounded. Keep container tightly closed. Keep in a cool, well-ventilated place. Combustible materials should be stored away from extreme heat and away from strong oxidizing agents.

Section 8. Exposure controls/personal protection

Exposure limits	Titanium Dioxide	ACGIH TLV (United States, 1/2007). TWA: 10 mg/m ³ 8 hour(s). OSHA PEL (United States, 11/2006). TWA: 15 mg/m ³ 8 hour(s). Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hour(s). Form: Total dust
	Silica, Gel	OSHA PEL 1989 (United States, 3/1989). TWA: 6 mg/m ³ 8 hour(s).
	Silica, Amorphous	NIOSH REL (United States, 12/2001). TWA: 6 mg/m ³ 10 hour(s).
	Aluminum Hydroxide	ACGIH TLV (United States, 2007). Notes: Total Respirable TWA: 10 mg/m ³ Form: Aluminum metal and insoluble compounds OSHA PEL (United States). TWA: 5 mg/m ³ Form: Respirable fraction TWA: 15 mg/m ³ Form: Total particulates
	Aluminum Oxide	OSHA PEL (United States, 11/2006). TWA: 5 mg/m ³ ACGIH TLV (United States, 11/2006). TWA: 15 mg/m ³
	Zirconium Oxide	OSHA PEL (United States). Notes: Total TWA: 5 mg/m ³ ACGIH TLV (United States). Notes: Total TWA: 5 mg/m ³

Engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Provide adequate safety showers and eyewashes in the area of use.
----------------------	--

Personal protection	<p>Personal protective equipment may vary depending on the job being performed.</p> <p>Eye/Face: Wear eye protection such as safety glasses with side shields, splash goggles or face shield with safety glasses.</p> <p>Skin: Avoid skin contact. Impervious gloves should be worn. Other items may include long sleeves, lab coats, or impervious jackets.</p> <p>Respiratory: Determine if airborne concentrations are below the recommended exposure limits in accordance your company's PPE program and regulatory requirements. If they are not, select a NIOSH-approved respirator that provides adequate protection from the concentration levels encountered. Air-purifying respirators are generally adequate for organic vapors. Use positive pressure, supplied-air respirators if there is potential for an uncontrolled release, if exposure levels are unknown, or under circumstances where air-purifying respirators may not provide adequate protection.</p> <p>Reference OSHA 29 CFR 1910.134</p>
---------------------	---

Personal protection in case of a large spill	Chemical resistant gloves, full protective suit, and boots. Respiratory protection in accordance with OSHA regulation 29 CFR 1910.134. A self-contained breathing apparatus should be used to avoid inhalation of the product vapors.
--	---

Section 9. Physical and chemical properties

Physical state	Paste/Dispersion.
Color	White.
Odor	Mild.
Molecular weight (g/mol)	Not available.
Boiling point	>400°F (204°C)
Melting point	Not available.
pH (1% soln/water)	Not applicable.
Vapor pressure	Not established
Vapor density	Not established.

Section 9. Physical and chemical properties

Specific gravity	1.0 to 2.1
Water/oil dist. coeff.	Not available.
Evaporation rate	Not established.
Odor threshold	Not established
Solubility in water	Negligible.
Dispersibility properties	Not dispersed in water.

Section 10. Stability and reactivity

Stability	The product is stable as supplied.
Instability temperature	Not applicable.
Conditions of instability	Not applicable.
Incompatibility with various substances	No specific information is available in our database.
Corrosivity	Our database contains no additional remark on the corrosivity of this product

Section 11. Toxicological information

Toxicity to animals	Name	Result	Species	Dose	Exposure
	Titanium Dioxide	LD Intratracheal	Rat	>100 ug/kg	-
		LD50 Oral	Rat	>10000 mg/kg	-
		TDLo	Rat	1.6 mg/kg	-
		Intratracheal			
		TDLo	Rat	1.25 mg/kg	-
		Intratracheal			
		TDLo Oral	Rat	60 g/kg	-
		TDLo	Rat	5 mg/kg	-
		Intratracheal			

Special remarks on toxicity to animals No additional remark.

Special remarks on chronic effects on humans No additional remark.

Special remarks on other toxic effects on humans No additional remark.

Section 12. Ecological information

Ecotoxicity Not available.


Section 13. Disposal considerations

Waste disposal Recycle to process, if possible. Toxic characteristic metals may be present (see Section II).

Section 14. Transport information

DOT Not regulated.

Labels



TDG Not regulated.

IATA/IMDG IATA: Not Regulated.
IMDG: Not Regulated.

Additional information US regulations require the reporting of spills when the amount exceeds the Reportable Quantity (RQ) for specific components of this material. See CERCLA in Section 15, Regulatory Information, for the Reportable Quantities.

Section 15. Regulatory information

Other regulations This section does not reference all applicable regulatory compliance lists.

TSCA: All ingredients are listed or compliant with TSCA.

DSL: All ingredients are listed or compliant with the NSNR.

SARA 302 component(s): None.

SARA 313 component(s): None.

CERCLA(RQ): None.

Section 16. Other information

Prepared by AOC, LLC - Corporate Regulatory Affairs.

DTN; ON

LEGAL DISCLAIMER

The information contained in this data sheet is furnished in good faith and without warranty, representation, or inducement or license of any kind, except that it is accurate to the best of AOC, LLC's knowledge, or was obtained from sources believed by AOC, LLC to be reliable. The accuracy, adequacy or completeness of health and safety precautions set forth herein cannot be guaranteed, and the buyer is solely responsible for ensuring that the product is used, handled, stored, and disposed of safely and in compliance with applicable federal, state or provincial, and local laws. AOC, LLC disclaims liability for any loss, damage or personal injury that arises from, or is in any way related to, use of the information contained in this data sheet.